

D6™

6-STAGE HVLP SPRAY SYSTEM



PAIR IT WITH YOUR FAVORITE FUJI SPRAY GUN

#4006-T70	T70™ Bottom Feed
#4106-T75G	T75G™ Gravity Feed
#GXPC-4106	G-XPC™ Side Mounted Gravity Feed



Unmatched Precision. Unbeatable Efficiency. Undiluted.

Fuji Spray®'s **D6** sets a new benchmark in the spray finishing industry, offering a powerful 6-stage motor rated at 11.5 PSI, engineered for efficient and cooler operation to prolong motor life and maximize return on investment. With 6 pre-set pressure settings, users gain precise control over spray output, ensuring professional-grade results with minimal overspray and waste. Providing consistently warm dry air, the **D6** atomizes even the highest viscosity coatings with virtually no thinning required, achieving stunning finishes and even coverage. The **D6** system is designed and assembled in Canada, built with a rugged design to ensure unmatched longevity whether being used in the workshop or at the job site.

SPECIFICATIONS

Weight	25.57 lbs.
Dimensions	18 x 15 x 11 in.
Hose Length	30 ft. with quick-connect and air control valve
Inside Hose Diameter	¾ in.
Hose Connection Type	Turbine - Threaded/ Spray Gun - Quick Connect
Filtration	Foam & HEPA (2-Stage)
Voltage	110V or 120V
PSI (Sealed Pressure)	Max 11.5. PSI

KEY FEATURES

- Powerful 6 Stage Motor
- Smart Select Control Panel with PSI settings ranging from 3 PSI (1-stage) to 11.5 PSI (6-stage)
- Easy Pause Remote Control (Remote range: 75 ft)
- Advanced 2-Stage Turbo Filtration with Check Filter Light
- Heat Dissipation Technology
- Fold Away Spray Gun Holder
- Versatile Applications
- 2 + 1 Year Warranty on Parts and Labor